



Technical Bulletin 00405

www.jcm-american.com

The JCM web site provides the tools you need, including the software information database with DIP switch information, our photo parts catalog, online ordering form, repair service, and more.

Parts are Parts



Part No. 052508

Description: Bushing

Usage: These bushings are located at the ends of the shafts that drive the belts in the WBA-10/11/12/13 transports.

Note: Worn or dirty bushings can slow down the transport. The bushings get dirty from dust and airborne contaminants. Applying any kind of lubrication to solve the problem will only make it worse, because the lubricant attracts more contaminants.

The solution is to disassemble the transport and clean the bushings and shafts. If the bushings show signs of scoring or are deformed, replace them.

JCM Latest Software Listing

Unit	ID	Version*	Chksums
WBA-10-SS	ID-003	V-3.10-20	4D54
WBA-10-SS	ID-022/023	V-3.10-03	C1BF
WBA-10-SS	ID-024	V-3.04-20	5271
WBA-11-SS	ID-003	V-3.10-20	4D54
WBA-11-SS	ID-022/023	V-3.10-03	C1BF
WBA-11-SS	ID-024	V-3.04-20	5271
WBA-12-SS	ID-003	V-3.09-20i	73F1
WBA-12-SS	ID-0C3	V-3.09-09i	766C
WBA-12-SS	ID-022/023	V-3.10-03i	0093
WBA-12-SS	ID-044C	V-3.10-05i	320E
WBA-12-SS	ID-044	V-3.10-05i	FE51
WBA-12-SS	ID-023B	V-3.00-04i	10C5
WBA-12-SS	ID-024	V-3.08-27	4DE9
WBA-13-SS	ID-003	V-3.09-20i	73F1
WBA-13-SS	ID-0C3	V-3.09-09i	766C
WBA-13-SS	ID-022/023	V-3.10-03i	0093
WBA-13-SS	ID-044C	V-3.10-05i	320E
WBA-13-SS	ID-044	V-3.10-05i	FE51
WBA-13-SS	ID-023B	V-3.00-04i	10C5
WBA-13-SS	ID-024	V-3.08-27	4DE9
DBV-200-B0/B1	ID-022/023	V-2.40-04-03	49E5
DBV-200-A2/A3	ID-004/BAR	V-2.40-05	FFA3
DBV-200-A2/A3	ID-044P/045P	V-2.40-05	FCBE
DBV-200-A2/A3	ID-011/015	V-2.40-09	CA98
DBV-200-A2/A3	ID-044/045W	V-2.40-05	FCBE
DBV-200-B4/B5	ID-024	V-2.40-09	7733
DBV-200-B4,B5	ID-003	V-2.40-02	C62B

The list of JCM bill validator software provided herein notifies customers of the latest versions developed. However, the listing does not identify versions approved by gaming jurisdictional authorities for actual use. Customers should consult JCM's Customer Service/Parts Sales departments concerning approved versions for jurisdictions of intended use.

* i suffix indicates Intelligent Cash Box option.

Save Time and Labor with JCM's Intelligent Cash Box System

The ICB[®] (Intelligent Cash Box) system is a unique cash box/cash flow management system that allows the operator to track a cash box and its contents through the entire cash flow process. The ICB system eliminates the need for dedicating cash boxes to specific machines, or putting barcode identification on the cash boxes. The cash boxes are tracked electronically eliminating most variance issues.






FREE REGIONAL TRAINING
 Give your techs the tools they need to keep your customers happy and your equipment running at peak efficiency. Call for information.

June
 June
 June
 July
 July

Reno
 Atlantic City
 Ft. Lauderdale
 Chicago
 N. California

Customer Notification/Tech Tips:

Question: What type of lubricant can I use on my JCM equipment?



Answer: Do not use any Petroleum (WD-40; Sewing Machine Oil), Citrus Oil (Orange, Lemon) or Powder (Graphite) based lubricants on our product.

Petroleum and Citrus Oil based lubricants: These types of lubricants can have two different impacts on our product:

- 1) The petroleum/oil contained within these solutions can have an effect on the physical material we use in the manufacture of our product (e.g. Cloudy lenses; damage to belts; dissolved plastic)
- 2) The lubricant also may not dissolve, so it gathers paper fiber and dust/debris inside the unit. This turns the lubricant into a liquid based sand paper that grinds away at the components that were originally being lubricated.

Powder based lubricants (Graphite): These types of lubricants can leave a residue inside the units. The excess powder that falls away from the lubricated components can create other issues within the product like damage to the motors and creation of static/conductive bridges on boards that can cause shorting.

For additional information on resolving technical issues, contact the JCM Technical Support Help Desk at (800) 683-7248.

JCM is a registered trademark of JCM American Corporation. All other product names mentioned herein may be registered trademarks or trademarks of their respective companies. Furthermore, TM and ® are not mentioned in each case in this publication.

JCM American Corporation
 925 Pilot Road
 Las Vegas, NV 89119
 Telephone: (702) 651-0000
 Toll Free: (800) 683-7248
 FAX (702) 651-0003
 www.jcm-american.com

