

BlueWave™ 2.0



EASY FIRMWARE UPDATING

- Portable, handheld device uploads firmware at the gaming device

FAST TRANSFER

- Quickly upload firmware via USB or Serial

INTERCHANGABLE SD CARDS

- Fast USB connection transfers firmware from an SD Card for most JCM products

ALWAYS READY

- Powered by two AA batteries

RIDE THE WAVE OF HIGH-SPEED DATA TRANSFER WITH THE BLUEWAVE 2.0 FROM JCM GLOBAL®

This amazing handheld tool is the perfect and easy way to load and upgrade your validator firmware right at the machine.

Lightweight and powerful, the BlueWave 2.0 easily connects via USB or Serial interface and gets you up and running again in seconds.

BlueWave™ 2.0

portable firmware upload tool

LOAD SPEED

- USB: 35-200 sec (depending on file size)
- Serial: 3-5 mins @ 38400 BAUD

INTERFACE

- USB 1.1 or 2.0
- RJ-45 to Serial adapter harness

PROGRAM MEMORY

- SD and SDHC

DIMENSIONS (WXDXH)

- 177.79 x 85.09 x 31.75mm (7 x 3.35 x 1.25")

WEIGHT

- 226.8 grams (0.50 lbs)

ENVIRONMENT

- Operation: 5 °C to 45 °C (41 to 113 °F)
- Operating Humidity: 30% to 80%
- Storage: -20 °C to 60 °C (-4 to 140 °F)
- Storage Humidity: 15% to 95% RH

SUPPLY VOLTAGE

- 2 AA size alkaline batteries (3.0V)

DESCRIPTION

- ASSY, BLUEWAVE DT-200
- KIT, BLUEWAVE 2.0
- KIT, BLUEWAVE 2.0, WBA
- KIT, BLUEWAVE 2.0, PUB/TAIKO
- KIT, BLUEWAVE 2.0 EBA-3x
- KIT, BLUEWAVE 2.0 DBV-30x



JCM American Corporation
925 Pilot Road
Las Vegas, NV 89119
USA
Tel: 800-683-7248
(800# for USA, Canada & Mexico)
Tel: 702-651-0000

Japan Cash Machine Co., Ltd.
N2-23-2, Higashi Nihonbashi,
Chuo-ku
Tokyo 103-0004
Japan
Tel: 81-3-5962-3731

JCM Europe GmbH
Mundelheimer Weg 60
D-40472 Dusseldorf
Germany
Tel: 49-211-530645-0

